

VANTAGE 3 SERIES TERMINAL

PRODUCT DATA SHEET

With the Vantage 3 Terminal, you can boost productivity, improve accuracy, and enhance customer satisfaction, all while maintaining the highest levels of traceability and compliance.



Power.

- Supply Voltage Range
1/N/PE AC 100 - 240 V 50 - 60 Hz
- Fuse Rating: 3A
- Power Consumption: 200 - 240 VA
- Equipment Classification: Class 1

Interface.

- 2 x Ethernet 10BASE-T, 100BASE-TX and 1000BASE-T
- 2 x USB Type 2.0
- 3 x RS232 Serial Interface

Regulatory.

- CE / UKCA

Hardware.

- 15" TFT LCD Resistant Touch Operation
- Stainless Steel 304 Corrosion Proof Enclosure
- IP66-Rated (NEMA 4X) Water and Dust Ingress Protection
- -5°C to +35°C Wide Operating Temperature Range
- Fanless Operation with Intel® Celeron® N3150/ N3160 or similar
- 128GB SATA SSD Minimum
- Wireless Network Connectivity
 - WiFi
 - Bluetooth
- 100 - 240 V AC Power Input
- M12 Type Input/Output Connectors
- 100mm VESA Mount

Corded/Cordless Ultra Scanner.

Introducing the ultimate scanner for the toughest environments.



Additional Information

- Warranty: 1 Year
- Support: Manufacturer support for at least 5 years.